

High Pressure Pump Units (Rental)

Water Blasting HP Unit - Electric Driven



Dimension	(L)2,500 (W)1,300 (H)1,900
Ex / ATEX	Offshore, Zone 2
Lifting / handling	DNV 2.7-1 lifting and forklift pockets
Max. pressure	800 bar
Flow	22 l/min
Power supply	380-690 VAC 50/60 Hz
Recc. fuse	63A
Air supply	1" Chicago clawcoupling
Outlet	1/2" BSP
Inlet	1" Chicago clawcoupling

Water Blasting UHP Unit - Electric Driven



Dimension	(L)2,500 (W)1,300 (H)1,900
Ex / ATEX	Offshore, Zone 2
Lifting / handling	DNV 2.7-1 lifting and forklift pockets
Max. pressure	2,000 bar
Flow	11 l/min
Power supply	380-690 VAC 50/60 Hz
Recc. fuse	63A
Air supply	1" Chicago clawcoupling
Outlet	9/16" AEHP FM
Inlet	1" Chicago clawcoupling

High Pressure Pump Units (Rental)

Water Blasting UHP Unit - Diesel Driven



Dimension	(L)2,500 (W)1,500 (H)1,900	
Ex / ATEX	Non-ATEX	
Lifting / handling	Pad - eyes and forklift pockets	
Max. pressure	2,000 bar	1,000 bar
Flow	25 l/min	50 l/min
Air supply	1" Chicago clawcoupling	
Outlet	9/16" AEHP FM	
Inlet	1" Chicago clawcoupling	
12V electric start Can be delivered as 1,000 bar unit or 2,000 bar unit		

Den-JET CE40 Water Blasting UHP Unit - Electric Driven



Dimension	(L)1,600 (W)1,050 (H)1,150		
Ex / ATEX	Non-ATEX		
Lifting / handling	DNV 2.7-1 lifting and forklift pockets		
Max. pressure	2,000 bar	800 bar	500 bar
Flow	10 l/min	22 l/min	35.5 l/min
Outlet connection	9/16" AEHP	1/2" BSP male	1/2" BSP male
Power supply	440 VAC 50Hz		
Recc. fuse	63A		
Inlet	1" Chicago clawcoupling		
3 different types, see pressure and flow above			

High Pressure Pump Units (Rental)

Ultra High Pressure Pump - Diesel



Dimension	(L)4,900 (W)2,200 (H)2,400	
Ex / ATEX	Offshore, Zone 2	
Lifting / handling	DNV 2.7-1 lifting and forklift pockets	
Max. pressure	2,800 bar	1,000 bar
Flow	40 l/min	110 l/min
Power supply	230 VAC 50/60 Hz	
Recc. fuse	10A	
Air supply	1" Chicago clawcoupling	
Outlet	9/16" AEHP FM @ 2,800 bar / M24 @ 1,000 bar	
Inlet	2" cam or 2x1" Chicago clawcoupling	
Diesel driven UHP pump for use with water		

Ultra High Pressure Pump - Diesel



Dimension	(L)3,900 (W)1,900 (H)2,200
Ex / ATEX	Offshore, Zone 2
Lifting / handling	DNV 2.7-1 lifting and forklift pockets
Max. pressure	1,000 bar
Flow	90 l/min
Power supply	230 VAC 50/60Hz
Recc. fuse	10A
Air supply	1" Chicago clawcoupling
Outlet	1/2" BSP male
Inlet	2x1" Chicago clawcoupling
Diesel driven HP pump for use with water	

High Pressure Pump Units (Rental)

Ultra High Pressure Pump - Diesel



Dimension	(L)2,990 (W)2,430 (H)2,675	
Ex / ATEX	Offshore, Zone 2	
Lifting / handling	DNV 2.7-1 lifting and forklift pockets	
Max. pressure	2,000 bar	1,000 bar
Flow	25 l/min	50 l/min
Power supply	230 VAC 50/60 Hz	
Recc. fuse	10A	
Air supply	1" Chicago clawcoupling	
Outlet	9/16" AEHP (1/2" BSP @ 1,000 bar)	
Inlet	1" Chicago clawcoupling	
Diesel driven HP pump for use with water		

High Pressure Pump - Electric



Dimension	(L)2,991 (W)2,438 (H)2,591		
Ex / ATEX	Offshore, Zone 2		
Lifting / handling	DNV 2.7-1 lifting and forklift pockets		
Max. pressure	2,500 bar	1,000 bar	
Flow	21 l/min	62 l/min	
Power supply	440 VAC 50/60 Hz	690 VAC 50/60 Hz	230V
Recc. fuse	250A	125A	16A
Outlet	M30 AEHP	1" cam LP	1.5 cam LP
Inlet	1" Camlock water	1" claw (air)	