

Specification Sheet

20 Way Hydraulic Power Unit

proserv

20 function workover control panel.

11 functions 5k and 9 functions 10k.

Fluid circulation pump with 3micron filters and sampling points.

Digital flowmeter for LP and HP line and a built in 15k psi chart recorder.

HPU is fitted with hotstab connection HP LP and return.



Technical details

Reservoir	700 litres	Haskel low pressure pump (2 sets)		Haskel nitrogen pump	
Low pressure accumulator	4 each x 37 litres	Assembly no	AW-60	Model number	ACD-62
Low pressure max working pressure	5,000 psi	Nominal ratio	60:1	Type	Single stage double acting
High pressure accumulator	2 each x 12 litres	Max pressure	9,800 psi liquid	Max gas in	9,000 psi
High pressure max working pressure	10,000 psi	Date manufactured	August 2007	Max gas out	9,000 psi
LP and HP pumps (two each)	Haskel air driven pump	Haskel high pressure pump (2 sets)		Oaler Fawcett Christie Cylinder (2 sets) High Pressure Side	
Lighting	220 volts	Assembly & serial no	AW-100 / 807-921	Charged to	4,200 psi
Tare weight	3,500 kg	Nominal ratio	100:1	Size	12 litres
Net weight	1,500 kg	Max pressure	16,500 psi liquid	Model	1205k-DC-694
Gross weight	5,000 kg	Date manufactured	August 2007	Max working pressure	690 bar
Proof load	10,000 kg	Haskel Circulating Pump		Oaler Fawcett Christie Cylinder (2 sets) Low Pressure Side	
Dimensions	320 x 250 x 270 cm	Assembly number	ATV-4	Charged to	2,300 psi
Standards	LLoyds Bs 7072 / IEE	Nominal ratio	4:1	Size	37 litres
Rated zone	Zone 1	Max pressure	1200 psi liquid	Model	AC-3703F-CZ-344
		Manufacture	August 2007	Max working pressure	345 bar